

P/N MS21250-06038

Description

Fastener Length: 3-1/64", Thread: 3/8-24, Thread Length: 41/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2125006038

Minimum Qty (MOQ):

NSN: 5306-00-420-6471

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS21250-06038 Specifications

Thread Class: Thread Direction: Right-hand O.635 Inches Minimum And O.655 Inches Maximum Fastener Length: O.035 Inches Nominal Head Style: Double Hexagon W/hole Head Height: O.388 Inches Nominal Width Between Flats: O.430 Inches Minimum And O.439 Inches Maximum Extended Washer Diameter: O.639 Inches Minimum And O.649 Inches Maximum
Thread Length: Fastener Length: Double Hexagon W/hole Head Height: 0.430 Inches Minimum And 0.655 Inches Maximum 0.635 Inches Maximum 3.020 Inches Nominal Double Hexagon W/hole 0.388 Inches Nominal 0.430 Inches Minimum And 0.439 Inches Maximum
Fastener Length: Head Style: Double Hexagon W/hole Head Height: 0.388 Inches Nominal Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum
Head Style: Head Height: 0.388 Inches Nominal Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum
Head Height: 0.388 Inches Nominal Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum
Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter: 0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness: 0.091 Inches Nominal
Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter: 0.375 Inches
Grip Length: 2.365 Inches Minimum And 2.385 Inches Maximum
Thread Quantity Per Inch: 24
Minimum Tensile Strength: 180000 Pounds Per Square Inch
Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material: Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And
Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/MS21250-06038 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/MS21250-06038 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/MS21250-06038 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/ms21250-06038 and selecting the quantity you want then