

Description

length: 3.395", grip: 2.75", thread: 3/8-24, external wrenching, flanged, 12 point, cadmium plated steel alloy, undrilled head, MS21250 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125006044
Minimum Qty (MOQ):	2
NSN:	5306-01-334-4205
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-06044 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.645 Inches Nominal
Fastener Length:	3.395 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.740 Inches Minimum And 2.760 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-06044> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.