

Description

Fastener Length: 3-41/64", Thread: 3/8-24, Thread Length: 21/32", MS21250 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125006048
Minimum Qty (MOQ):	5
NSN:	5306-00-177-5506
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-06048 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum And 0.665 Inches Maximum
Fastener Length:	3.635 Inches Minimum And 3.655 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.378 Inches Minimum And 0.398 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.081 Inches Minimum And 0.101 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.990 Inches Minimum And 3.010 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Primary Washer
Material:	Steel Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-06048> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.