

P/N MS21250-06052

Description

Fastener Length: 3-57/64", Thread: 3/8-24, Thread Length: 41/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125006052
Minimum Qty (MOQ):	2
NSN:	5306-00-040-9749
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21250-06052 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.635 Inches Minimum And 0.655 Inches Maximum
Fastener Length:	3.895 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	3.240 Inches Minimum And 3.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hardness Rating:	39.0 Rockwell C Minimum And 43.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/MS21250-06052 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.