

Description

Fastener Length: 1-21/32", Thread: 7/16-20, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125007015
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-420-8611
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS21250-07015 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.721 Inches Nominal
Fastener Length:	1.6585 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.435 Inches Nominal
Width Between Flats:	0.500 Inches Nominal
Extended Washer Diameter:	0.745 Inches Nominal
Extended Washer Thickness:	0.099 Inches Nominal
Grip Diameter:	0.436 Inches Nominal
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	0.9375 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty2cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-07015> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.