

Description

Fastener Length: 1-3/4", Thread: 7/16-20, Thread Length: 3/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125007016
Minimum Qty (MOQ):	1
NSN:	5306-00-901-4299
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21250-07016 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.721 Inches Minimum And 0.761 Inches Maximum
Fastener Length:	1.731 Inches Minimum And 1.751 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.425 Inches Minimum And 0.445 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Extended Washer Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Extended Washer Thickness:	0.089 Inches Minimum And 0.109 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-07016> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.