

Description

Fastener Length: 4-63/64", Thread: 3/8-20, Thread Length: 49/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125007068
Minimum Qty (MOQ):	1
NSN:	5306-01-413-9249
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS21250-07068 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.721 Inches Minimum And 0.768 Inches Maximum
Fastener Length:	4.981 Inches Minimum And 5.001 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.435 Inches Nominal
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Extended Washer Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Extended Washer Thickness:	0.099 Inches Nominal
Nominal Thread Diameter:	0.437 Inches
Grip Length:	4.490 Inches Minimum And 4.510 Inches Maximum
Thread Quantity Per Inch:	20
Material:	Steel Comp 8740 Overall And Steel Comp 4140 Overall And Steel Comp E4340 Overall And Steel Comp 6150 Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-07068> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.