



Military-Fasteners.com

P/N MS21250-07074

## Description

Fastener Length: 5-23/64", Thread: 3/8-20, Thread Length: 47/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS2125007074
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-334-0517
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS21250-07074 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.741 Inches Nominal
Fastener Length:	5.366 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.435 Inches Nominal
Width Between Flats:	0.500 Inches Nominal
Extended Washer Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Extended Washer Thickness:	0.099 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.437 Inches
Grip Length:	4.615 Inches Minimum And 4.635 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-07074> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.