

Description

Fastener Length: 5-47/64", Thread: 7/16-20, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125007080
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-424-3243
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS21250-07080 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.721 Inches Nominal
Fastener Length:	5.741 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.435 Inches Nominal
Width Between Flats:	0.500 Inches Nominal
Extended Washer Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Extended Washer Thickness:	0.099 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	5.000 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	23200 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-07080> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.