

Description

Fastener Length: 2-13/32", Thread: 1/2-20, Thread Length: 49/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2125008026
Minimum Qty (MOQ):	1
NSN:	5306-00-955-8273
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21250-08026 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.768 Inches Minimum
Fastener Length:	2.413 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.504 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Extended Washer Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Extended Washer Thickness:	0.123 Inches Nominal
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.625 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-08026> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.