



Military-Fasteners.com

P/N MS21250-09030

Description

Fastener Length: 2-", Thread: 1/2-18, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125009030
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-224-9320
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-09030 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.862 Inches Minimum And 0.882 Inches Maximum
Fastener Length:	2.747 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.557 Inches Nominal
Width Between Flats:	0.616 Inches Minimum And 0.627 Inches Maximum
Extended Washer Diameter:	0.928 Inches Minimum And 0.938 Inches Maximum
Extended Washer Thickness:	0.133 Inches Nominal
Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	1.865 Inches Minimum And 1.885 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-09030> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.