

Description

Fastener Length: 3", Thread: 1/2-18, Thread Length: 7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125009048
Minimum Qty (MOQ):	1
NSN:	5306-00-047-3457
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21250-09048 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.862 Inches Minimum And 0.882 Inches Maximum
Fastener Length:	3.872 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.557 Inches Nominal
Width Between Flats:	0.616 Inches Minimum And 0.627 Inches Maximum
Extended Washer Diameter:	0.928 Inches Minimum And 0.938 Inches Maximum
Extended Washer Thickness:	0.133 Inches Nominal
Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	2.990 Inches Minimum And 3.010 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-09048> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.