



Military-Fasteners.com

P/N MS21250-09056

Description

Fastener Length: 4-", Thread: 1/2-18, Thread Length: 27/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125009056
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-955-8690
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21250-09056 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.852 Inches Minimum
<b>Fastener Length:</b>	4.372 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.557 Inches Nominal
<b>Width Between Flats:</b>	0.616 Inches Minimum And 0.627 Inches Maximum
<b>Extended Washer Diameter:</b>	0.928 Inches Minimum And 0.938 Inches Maximum
<b>Extended Washer Thickness:</b>	0.133 Inches Nominal
<b>Grip Diameter:</b>	0.5605 Inches Minimum And 0.5615 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.562 Inches
<b>Grip Length:</b>	3.500 Inches Nominal
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-09056> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.