

**Description**

Fastener Length: 3-17/32", Thread: 5/8-18, Thread Length: 59/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS2125010042](#)

SKU / Model:	MS2125010042
Minimum Qty (MOQ):	2
NSN:	5306-00-150-3486
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21250-10042 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.909 Inches Minimum And 0.929 Inches Maximum
<b>Fastener Length:</b>	3.544 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.618 Inches Nominal
<b>Width Between Flats:</b>	0.679 Inches Minimum And 0.690 Inches Maximum
<b>Extended Washer Diameter:</b>	1.040 Inches Minimum And 1.050 Inches Maximum
<b>Extended Washer Thickness:</b>	0.150 Inches Nominal
<b>Grip Diameter:</b>	0.6230 Inches Minimum And 0.6240 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Grip Length:</b>	2.615 Inches Minimum And 2.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-10042> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.