

Description

Fastener Length: 2-7/8", Thread: 3/4-16, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125012030
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-765-3354
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21250-12030 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.046 Inches Minimum And 1.066 Inches Maximum
Fastener Length:	2.931 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.711 Inches Nominal
Width Between Flats:	0.803 Inches Minimum And 0.814 Inches Maximum
Extended Washer Diameter:	1.220 Inches Minimum And 1.230 Inches Maximum
Extended Washer Thickness:	0.178 Inches Nominal
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.865 Inches Minimum And 1.885 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-12030> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.