

**Description**

Fastener Length: 2-7/8", Thread: 3/4-16, Thread Length: 1-1/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2125012030
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-765-3354
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21250-12030 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.046 Inches Minimum And 1.066 Inches Maximum
<b>Fastener Length:</b>	2.931 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.711 Inches Nominal
<b>Width Between Flats:</b>	0.803 Inches Minimum And 0.814 Inches Maximum
<b>Extended Washer Diameter:</b>	1.220 Inches Minimum And 1.230 Inches Maximum
<b>Extended Washer Thickness:</b>	0.178 Inches Nominal
<b>Grip Diameter:</b>	0.7480 Inches Minimum And 0.7490 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	1.865 Inches Minimum And 1.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-12030> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.