

Description

Fastener Length: 3-29/64", Thread: 3/4-16, Thread Length: 1-3/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2125012038
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-313-9204
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21250-12038 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.053 Inches Minimum And 1.103 Inches Maximum
Fastener Length:	3.438 Inches Minimum And 3.468 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.590 Inches Minimum And 0.610 Inches Maximum
Extended Washer Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Extended Washer Thickness:	0.098 Inches Minimum And 0.118 Inches Maximum
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Head Minor Diameter:	0.797 Inches Minimum And 0.812 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.365 Inches Minimum And 2.385 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-12038> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.