

Description

Fastener Length: 3-15/16", Thread: 3/4-16, Thread Length: 1-1/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125012046
Minimum Qty (MOQ):	1
NSN:	5306-01-039-0234
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-12046 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.036 Inches Minimum And 1.076 Inches Maximum
Fastener Length:	3.921 Inches Minimum And 3.941 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.701 Inches Minimum And 0.721 Inches Maximum
Width Between Flats:	0.812 Inches Nominal
Extended Washer Diameter:	1.220 Inches Minimum And 1.230 Inches Maximum
Extended Washer Thickness:	0.178 Inches Nominal
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.865 Inches Minimum And 2.885 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-12046> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.