

Description

Fastener Length: 3-3/8", Thread: 7/8-14, Thread Length: 1-17/64", MS21250 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125014034
Minimum Qty (MOQ):	1
NSN:	5306-00-508-7044
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21250-14034 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.254 Inches Minimum And 1.274 Inches Maximum
Fastener Length:	3.389 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.808 Inches Nominal
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Extended Washer Diameter:	1.428 Inches Minimum And 1.438 Inches Maximum
Extended Washer Thickness:	0.198 Inches Nominal
Grip Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
End Item Identification:	Aircraft, (Ac-130h, Mc-130h, Ec-130e, Hc-130);aircraft, Hercules C-
Nominal Thread Diameter:	0.875 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-14034> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.