

Description

Fastener Length: 3-33/64", Thread: 7/8-14, Thread Length: 1-9/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2125014036
Minimum Qty (MOQ):	1
NSN:	5306-01-113-9760
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21250-14036 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.244 Inches Minimum And 1.284 Inches Maximum
Fastener Length:	3.504 Inches Minimum And 3.524 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.798 Inches Minimum And 0.818 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.948 Inches Maximum
Extended Washer Diameter:	1.428 Inches Minimum And 1.438 Inches Maximum
Extended Washer Thickness:	0.188 Inches Minimum And 0.208 Inches Maximum
Grip Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
Nominal Thread Diameter:	0.875 Inches
Grip Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-14036> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.