

**Description**

Fastener Length: 4-1/4", Thread: 7/8-14, Thread Length: 1-17/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2125014048
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-463-0230
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21250-14048 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.254 Inches Minimum And 1.274 Inches Maximum
<b>Fastener Length:</b>	4.264 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.808 Inches Nominal
<b>Width Between Flats:</b>	0.928 Inches Minimum And 0.940 Inches Maximum
<b>Extended Washer Diameter:</b>	1.428 Inches Minimum And 1.438 Inches Maximum
<b>Extended Washer Thickness:</b>	0.198 Inches Nominal
<b>Grip Diameter:</b>	0.8730 Inches Minimum And 0.8740 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.875 Inches
<b>Grip Length:</b>	2.990 Inches Minimum And 3.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	14
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-14048> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.