

## P/N MS21250H04010

## **Description**

Length: 1-1/8", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 33/64", MS21250 series bolt

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS21250H04010

Minimum Qty (MOQ):

NSN: 5306-00-400-0047

Schedule B: 7318.15.2000

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21250H04010 Specifications

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.502 Inches Minimum And 0.522 Inches Maximum  |
| Fastener Length:                               | 1.137 Inches Nominal   |
| Head Style:                                    | Double Hexagon W/hole  |
| Head Height:                                   | 0.300 Inches Nominal   |
| Width Between Flats:                           | 0.304 Inches Minimum And 0.313 Inches Maximum  |
| Extended Washer Diameter:                      | 0.428 Inches Minimum And 0.438 Inches Maximum  |
| Extended Washer Thickness:                     | 0.069 Inches Nominal   |
| Hole Diameter:                                 | 0.037 Inches Nominal   |
| Grip Diameter:                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum  |
| Nominal Thread Diameter:                       | 0.250 Inches   |
| Grip Length:                                   | 0.615 Inches Minimum And 0.635 Inches Maximum  |
| Hole Quantity:                                 | 4  |
| Hole Type:                                     | Drilled  |
| Thread Quantity Per Inch:                      | 28   |
| Minimum Tensile Strength:                      | 180000 Pounds Per Square Inch  |
| Hardness Rating:                               | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall  |
| Hole Configuration Style:                      | Round Longitudinal Hole  |
| Material:                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall  |
| Material Document And Classification:          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,cl 3 Fed Spec All Treatment Responses Overall  |
| Thread Series Designator:                      | Unjf   |

## **How to Order**

| $Order\ this\ shear\ bolt\ from\ our\ inventory\ online\ by\ visiting\ \underline{https://military-fasteners.com/bolts/shear+bolts/MS21250H04010}\ and\ selecting\ the\ quantity\ you\ wantable and\ selecting\ the\ quantable and\ quantable and\ selecting\ the\ quantable and\ q$ |
|---|
| then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
| Provided by Military-Fasteners.com  |