

# P/N MS21250H05006

Military-Fasteners.com

### Description

length: 0.974", grip: 0.375", thread: 5/16-24, external wrenching bolt, flanged, 12 point, cadmium plated steel alloy, drilled head

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS21250H05006
Minimum Qty (MOQ):	10
NSN:	5306-00-869-4205
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS21250H05006 Specifications

Thread Direction:Right-handThread Length:0.579 Inches Minimum And 0.619 Inches MaximumFasteer Length:0.664 Inches Minimum And 0.984 Inches MaximumHead Style:Double Hexagon W/holeHead Height:0.348 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumExtended Washer Diameter:0.362 Inches NominalBorben Berner:0.362 Inches NominalBorben Berner:0.362 Inches NominalBorben Berner:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 Inches NominalBorben Berner:0.312 Inches NominalNominal Thread Diameter:0.312 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 InchesBorben Berner:0.312 Inches Minimum And 0.3120 Inches MaximumHole Cyanity:4Hole Cyanity:4Hole Cyanity:4Hole Configuration Style:0.000 Pounds Per Square InchHole Configuration Style:30.00 Pounds Per Square InchHole Configuration Style:0.000 Pounds Per Square Inch 43.0 Rockwell C Maximum OverallHole Configuration Style:Souble Hexagon Longitudinal HoleMaterial:Seel Comp 874 Overall Or Stel Comp 140 Over	Thread Class:	3a
Thread Length:0.579 Inches Minimum And 0.619 Inches MaximumFastener Length:0.964 Inches Minimum And 0.984 Inches MaximumHead Style:Double Hexagon W/holeHead Height:0.348 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumExtended Washer Diameter:0.521 Inches Minimum And 0.316 Inches MaximumDouble Hexagon U/hole0.822 Inches NominalBetween Flats:0.862 Inches NominalBollameter:0.062 Inches NominalOne Diameter:0.062 Inches NominalBollameter:0.310 Inches Minimum And 0.3120 Inches MaximumOne Diameter:0.312 InchesOsigi Inches Minimum And 0.385 Inches MaximumBole Duameter:0.326 Inches Minimum And 0.385 Inches MaximumBole Quantity:4Hole Stype:DilledThread Quantity Per Inch:2Audres Rating:3.0.8 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Duable Hexagon Longitudinal HoleMaterial Response Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 3rdMaterial Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall Or Mil-s-5000 Mil Spec 3rdSurface Treatment:Cadmiu Overall And Chromate OverallSurface Treatment Courter AndMil-s-Ed Spigle Treatment Response OverallGrip Langthere:Cadmiu Overall And Chromate OverallBaterial Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmiu Overall And Chromate Ov		
Fastener Length:0.964 Inches Minimu And 0.984 Inches MaximumHead Style:Double Hexagon W/holeHead Style:0.348 Inches NominalHead Height:0.348 Inches Minimu And 0.376 Inches MaximumWidth Between Flats:0.367 Inches Minimu And 0.376 Inches MaximumExtended Washer Diameter:0.362 Inches Nominal0.062 Inches Nominal0.062 Inches NominalHole Diameter:0.062 Inches Minimum And 0.3120 Inches MaximumO.062 Inches Nominal0.062 Inches NominalHole Diameter:0.0311 Inches Minimum And 0.3120 Inches MaximumO.051 Inches Minimum And 0.3120 Inches Maximum0.312 InchesGrip Diameter:0.310 Inches Minimum And 0.385 Inches MaximumNominal Thread Diameter:0.312 InchesO.355 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Quantity:1Hole Quantity Per Inch:24Hole Configuration Style:Double Hexagon Longitudinal HoleMinimum Tensile Strength:180000 Pounds Per Squer InchHole Configuration Style:Double Hexagon Longitudinal HoleMaterial Document And Classification:Mil:s-6049 Mil Spec 1st Material Response Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Mil:s-5626 Mil Spec 2nd Material Response Overall Or Mil:s-5		
Head Style:Double Hexagon W/holeHead Height:0.348 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumExtended Washer Dlameter:0.521 Inches Minimum And 0.531 Inches MaximumBolt Diameter:0.082 Inches NominalHole Diameter:0.062 Inches NominalBolt Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.3120 Inches Minimum And 0.3120 Inches MaximumBolt Diameter:0.3120 Inches Minimum And 0.3120 Inches MaximumBolt Diameter:0.3120 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.3120 Inches Minimum And 0.3120 Inches MaximumBolt Diameter:0.3120 Inches Minimum And 0.3120 Inches MaximumBolt Diameter:0.312 InchesBolt Diameter:0.320 Inches Minimum And 0.3120 Inches MaximumHole Quantity:4Hole Stype:DifledBolt Diameter:10000 Pounds Per Square InchHole Guantity Per Inch:24Bolt Devell Evengen30.0 Rockwell C Maximum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Duble Hexagon Longitudinal HoleHole Configuration Style:Duble Hexagon Longitudinal HoleMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5609 Mil Spec 1st Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Cadmium Ove	-	
Head Height:0.348 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumExtended Washer Diameter:0.521 Inches Minimum And 0.531 Inches MaximumBetweended Washer Thickness:0.521 Inches NominalBole Diameter:0.062 Inches NominalGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 Inches Minimum And 0.3120 Inches MaximumBole Quantity:0.355 Inches Minimum And 0.385 Inches MaximumHole Quantity:0.365 Inches Minimum And 0.385 Inches MaximumHole Type:DilledHole Outity:10000 Pounds Per Square InchHole Outity:9.0 Rockwell C Minimum Overall And 4.3.0 Rockwell C Maximum OverallHole Configuration Style:0.9.0 Rockwell C Minimum Overall And 4.3.0 Rockwell C Maximum OverallHole Configuration Style:0.9.0 Rockwell C Stat Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil-s-5626 Mil Spec 2 nd Material Response Overall Or Mil	-	
Width Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumExtended Washer Diameter:0.521 Inches Minimum And 0.531 Inches MaximumExtended Washer Thickness:0.082 Inches NominalHole Diameter:0.062 Inches NominalObject Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumObject Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.365 Inches Minimum And 0.3120 Inches MaximumHole Quantity:0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Quantity:1Hole Quantity:1Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:3.9.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Steal Comp 8740 Chromate Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6030 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Q-p-16 Ty2 Cl3 Fed Spec Single Treatment Response Overall		
Extended Washer Diameter:0.521 Inches Minimum And 0.531 Inches MaximumExtended Washer Thickness:0.082 Inches NominalHole Diameter:0.062 Inches NominalGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 InchesGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Type:DrilledDrilled24Minimum Tensile Strength:180000 Pounds Per Square InchHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall Or Mil-s-6030 Mil Spec 3rd Material Activation:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overa	Head Height:	0.348 Inches Nominal
Extended Washer Thickness:0.882 Inches NominalHole Diameter:0.062 Inches MominalGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 InchesO 3.12 Inches0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Type:DiriledHole Outstry:24Hong Starting:180000 Pounds Per Square InchHole Configuration Style:0.001e Hexagon Longitudinal HoleHole Configuration Style:Double Hexagon Longitudinal HoleMaterial Bocument And Classification:Stel Comp 8740 Overall Or Stel Comp 1400 Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Type Cisingle Treatment Response Overall	Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:0.062 Inches NominalGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 Inches0.312 Inches0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Quantity:1Hole Quantity:1Hole Quantity:24Hole Quantity Per Inch:80000 Pounds Per Square InchHardness Rating:9.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial Cocument And Classification:Steel Comp 8740 Overall Or Steel Comp 1440 Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Extended Washer Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Grip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumNominal Thread Diameter:0.312 InchesGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Quantity:0.118dHole Quantity:	Extended Washer Thickness:	0.082 Inches Nominal
Nominal Thread Diameter:0.312 InchesGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Quantity:DilledHole Type:DilledThread Quantity Per Inch:2Minimum Tensile Strength:18000 Pounds Per Square InchHole Configuration Style:0.000 Pounds Per Square InchHole Configuration Style:0.000 Pounds Per Square InchHaterlal:Stel Comp 8740 Overall And 43.0 Rockwell C Maximum OverallMaterlal Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Hole Diameter:	0.062 Inches Nominal
Grip Length:0.365 Inches Minimum And 0.385 Inches MaximumHole Quantity:4Hole Quantity:0Billed0Thread Quantity Per Inch:24Billow Do Pounds Per Square Inch80000 Pounds Per Square InchHardness Rating:9.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Gridmum Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 CJ3 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Hole Quanity:4Hole Quanity:1Hole Type:DrilledDrined Quanity Per Inch:24Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.312 Inches
Hole Type:DrilledThread Quantity Per Inch:24Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:24Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHardness Rating:Double Hexagon Longitudinal HoleHole Configuration Style:Double Hexagon Longitudinal HoleMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Hole Quantity:	4
Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall Oq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Hole Type:	Drilled
Hardness Rating:39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	24
Hole Configuration Style:Double Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Hole Configuration Style:	Double Hexagon Longitudinal Hole
Classification:Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall
Surface Treatment Document And Classification:	Material Document And Classification:	
Classification: Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/MS21250H05006</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.