

Description

Fastener Length: 1-7/32", Thread: 1/4-24, Thread Length: 39/64", MS21250 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21250H05010 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-00-510-5338 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21250H05010 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.589 Inches Minimum And 0.609 Inches Maximum |
| Fastener Length: | 1.224 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.348 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Extended Washer Diameter: | 0.521 Inches Minimum And 0.531 Inches Maximum |
| Extended Washer Thickness: | 0.082 Inches Nominal |
| Hole Diameter: | 0.055 Inches Nominal |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Cl 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250H05010> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.