

Description

Fastener Length: 1-15/32", Thread: 1/4-24, Thread Length: 39/64", MS21250 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21250H05014
Minimum Qty (MOQ):	5
NSN:	5306-00-482-4316
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21250H05014 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.589 Inches Minimum And 0.609 Inches Maximum
Fastener Length:	1.474 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.348 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Extended Washer Thickness:	0.082 Inches Nominal
Hole Diameter:	0.055 Inches Minimum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250H05014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.