

P/N MS21250H06012

Description

Fastener Length: 1-13/32", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 41/64",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS21250H06012

Minimum Qty (MOQ): 5

NSN: 5306-00-047-3436

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS21250H06012 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.635 Inches Minimum And 0.655 Inches Maximum
Fastener Length:	1.395 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/MS21250H06012 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.