

P/N MS21250H06018

Description

Fastener Length: 1-49/64", Hole Diameter: ", Thread: 3/8-24, Thread Length: 41/64

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS21250H06018

Minimum Qty (MOQ): 5

NSN: 5306-00-464-2639

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21250H06018 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.635 Inches Minimum And 0.655 Inches Maximum |
| Fastener Length: | 1.770 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.388 Inches Nominal |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Extended Washer Diameter: | 0.639 Inches Minimum And 0.649 Inches Maximum |
| Extended Washer Thickness: | 0.091 Inches Nominal |
| Hole Diameter: | 0.055 Inches Nominal |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.115 Inches Minimum And 1.135 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Round Longitudinal Hole |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/MS21250H06018 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/MS21250H06018 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/MS21250H06018 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/ms21250H06018 and selecting the quantity you want of the property of the pro