

Description

Fastener Length: 2-49/64", Hole Diameter: 3/64", Thread: 3/8-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21250H06034
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-262-6732
Schedule B:	7318.15.2010
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS21250H06034 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum
Fastener Length:	2.770 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.4375 Inches Nominal
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.3750 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Flats
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall And Aisi Assn Std 1st Material Response Overall Or Mil-s5000 Mil Spec 2nd Material Response Overall And Aisi Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall And Aisi Assn Std 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall And Aisi Assn Std 4th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250H06034> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.