

**Description**

Fastener Length: 5-1/8", Hole Diameter: 3/64", Thread: 3/8-20, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21250H07070                             |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-01-200-1408                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS21250H07070 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.721 Inches Minimum And 0.761 Inches Maximum   |
| <b>Fastener Length:</b>                               | 5.106 Inches Minimum And 5.126 Inches Maximum   |
| <b>Head Style:</b>                                    | Double Hexagon W/hole   |
| <b>Head Height:</b>                                   | 0.425 Inches Minimum And 0.445 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.500 Inches Nominal  |
| <b>Extended Washer Diameter:</b>                      | 0.740 Inches Minimum And 0.750 Inches Maximum   |
| <b>Extended Washer Thickness:</b>                     | 0.089 Inches Minimum And 0.109 Inches Maximum   |
| <b>Hole Diameter:</b>                                 | 0.050 Inches Minimum And 0.060 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.4360 Inches Minimum And 0.4370 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>                       | 0.437 Inches  |
| <b>Grip Length:</b>                                   | 4.365 Inches Minimum And 4.385 Inches Maximum   |
| <b>Hole Quantity:</b>                                 | 4   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 20  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall                                       |
| <b>Hole Configuration Style:</b>                      | Double Hexagon Longitudinal Hole  |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250H07070> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.