



Military-Fasteners.com

P/N MS21254-2LS

Description

left hand thread, short, turnbuckle eye end, locking clip

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS212542LS
Minimum Qty (MOQ):	1
NSN:	5340-00-069-0594
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21254-2LS Specifications

Thread Class:	3a Rod Connection
Thread Direction:	Left-hand Rod Connection
Thread Length:	0.328 Inches Minimum Rod Connection And 0.422 Inches Maximum Rod Connection
Hole Diameter:	0.190 Inches Nominal
Radius:	0.187 Inches Nominal
Shank Outside Diameter:	0.138 Inches Nominal
Tongue Width:	0.375 Inches Nominal
Tongue Thickness:	0.120 Inches Minimum And 0.130 Inches Maximum
Shank Overall Length:	1.175 Inches Nominal
Hole Shape:	Round
Distance From End To Hole Center:	1.485 Inches Minimum And 1.531 Inches Maximum
Nominal Thread Size:	0.138 Inches Rod Connection
Material:	Steel Comp 8630 Overall Or Steel Comp 4130 Overall
lil Material:	Steel Comp 8630 Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
Surface Treatment:	Chromium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Connector
Thread Series Designator:	Unf Rod Connection

How to Order

Order this rod end connector from our inventory online by visiting <https://military-fasteners.com/fittings/rod+end+connectors/MS21254-2LS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.