

Description

Thread Size: 1/4", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS212545RS
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-057-7184
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	011790, Aircraft Parts Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21254-5RS Specifications

Thread Class:	3a Rod Connection
Thread Direction:	Right-hand Rod Connection
Thread Length:	0.578 Inches Minimum Rod Connection And 0.672 Inches Maximum Rod Connection
Radius:	0.312 Inches Nominal
Shank Outside Diameter:	0.250 Inches Nominal
Tongue Width:	0.625 Inches Nominal
Tongue Thickness:	0.214 Inches Minimum And 0.224 Inches Maximum
Shank Overall Length:	1.328 Inches Nominal
Distance From End To Hole Center:	1.735 Inches Minimum And 1.781 Inches Maximum
Nominal Thread Size:	0.250 Inches Rod Connection
Material:	Steel Comp 8630 Overall Or Steel Comp 4130 Overall
lil Material:	Steel Comp 8630 Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
Surface Treatment:	Chromium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Connector
Thread Series Designator:	Unf Rod Connection

How to Order

Order this turnbuckle from our inventory online by visiting <https://military-fasteners.com/fittings/rod+end+connectors/MS21254-5RS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.