

Description

Thread Size: 1/4", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|----------------------------|
| SKU / Model: | MS212555LS |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-069-4926 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 011790, Aircraft Parts Noi |

NO IMAGE
AVAILABLE

P/N MS21255-5LS Specifications

| | |
|---|--|
| Thread Class: | 3a Rod Connection |
| Thread Direction: | Left-hand Rod Connection |
| Thread Length: | 0.578 Inches Minimum Rod Connection And 0.672 Inches Maximum Rod Connection |
| Radius: | 0.312 Inches Nominal |
| Shank Outside Diameter: | 0.250 Inches Minimum |
| Tongue Width: | 0.625 Inches Nominal |
| Tongue Thickness: | 0.214 Inches Minimum And 0.224 Inches Maximum |
| Shank Overall Length: | 1.238 Inches Nominal |
| Distance From End To Hole Center: | 1.735 Inches Minimum And 1.781 Inches Maximum |
| Nominal Thread Size: | 0.250 Inches Rod Connection |
| Material: | Steel Comp 8630 Overall Or Steel Comp 4130 Overall |
| lii Material: | Steel Comp 8630 Or Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Chromium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Connector |
| Thread Series Designator: | Unf Rod Connection |

How to Order

Order this turnbuckle from our inventory online by visiting <https://military-fasteners.com/bolts/eye+bolts/MS21255-5LS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.