

Description

5/16-24 left hand thread - 3/16" cable diameter - wire rope terminal - swaging - stud - long thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS212596LH
Minimum Qty (MOQ):	1
NSN:	4030-00-132-9195
National Motor Freight:	011790, Aircraft Parts Noi

NO IMAGE
AVAILABLE

P/N MS21259-6LH Specifications

Thread Class:	A3a
Thread Direction:	Left-hand
Inside Diameter:	0.203 Inches Minimum And 0.208 Inches Maximum
Thread Length:	1.443 Inches Minimum And 1.463 Inches Maximum
Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Undercut Diameter:	0.285 Inches Minimum And 0.313 Inches Maximum
Overall Length:	4.000 Inches Minimum And 4.018 Inches Maximum
Plain Shank Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Plain Shank Diameter:	0.354 Inches Minimum And 0.359 Inches Maximum
Accommodated Material Diameter:	0.188 Inches Nominal
Width Across Flats:	0.365 Inches Minimum And 0.385 Inches Maximum
Breaking Strength:	4200.0 Pounds Minimum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Surface Treatment:	Passivate
Style Designator:	Threaded
Thread Series Designator:	Unf

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21259-6LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.