

**Description**

6-40 right hand thread, 1/16" cable diameter, wire rope terminal, swaging, stud, long thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS21260-L2RH](#)

SKU / Model:	MS21260L2RH
Minimum Qty (MOQ):	5
NSN:	4030-00-580-6824
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



\* See page 2 for technical characteristics

## P/N MS21260L2RH Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Inside Diameter:</b>	0.078 Inches Minimum And 0.083 Inches Maximum
<b>Thread Length:</b>	0.332 Inches Minimum And 0.422 Inches Maximum
<b>Hole Diameter:</b>	0.063 Inches Minimum And 0.068 Inches Maximum
<b>Undercut Diameter:</b>	0.092 Inches Minimum And 0.098 Inches Maximum
<b>Overall Length:</b>	3.428 Inches Minimum And 3.554 Inches Maximum
<b>Plain Shank Length:</b>	0.969 Inches Minimum And 1.031 Inches Maximum
<b>Plain Shank Diameter:</b>	0.155 Inches Minimum And 0.160 Inches Maximum
<b>Accommodated Material Diameter:</b>	0.062 Inches Nominal
<b>Width Across Flats:</b>	0.062 Inches Nominal
<b>Breaking Strength:</b>	480.0 Pounds Minimum
<b>Thread Quantity Per Inch:</b>	40
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Threaded
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260L2RH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.