

Description

thread: 10-32 right hand, cable diameter 3/32", wire terminal, swaging, stud, long thread, MS21260 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------------------------------|
| SKU / Model: | MS21260L3RH |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4030-00-580-6794 |
| National Motor Freight: | 105200, Fittings Cable / Chain / Rope I / S |

NO IMAGE
AVAILABLE

P/N MS21260L3RH Specifications

| | |
|----------------------------------------------|-----------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Inside Diameter: | 0.119 Inches Nominal |
| Thread Length: | 0.453 Inches Minimum And 0.547 Inches Maximum |
| Hole Diameter: | 0.063 Inches Minimum And 0.068 Inches Maximum |
| Undercut Diameter: | 0.133 Inches Minimum And 0.139 Inches Maximum |
| Overall Length: | 3.675 Inches Minimum And 3.801 Inches Maximum |
| Plain Shank Length: | 1.188 Inches Minimum And 1.250 Inches Maximum |
| Plain Shank Diameter: | 0.213 Inches Minimum And 0.218 Inches Maximum |
| Accommodated Material Diameter: | 0.094 Inches Nominal |
| Width Across Flats: | 0.250 Inches Nominal |
| Breaking Strength: | 920.0 Pounds Minimum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Steel Comp 303se And Steel Comp 305 |
| Material Document And Classification: | 66 Fed Std All Material Responses |
| Surface Treatment: | Passivate |
| Style Designator: | Threaded |
| Thread Series Designator: | Unf |

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260L3RH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.