

Description

thread: 1/4-28 left hand, cable diameter: 1/8", swaging, stud, long thread, MS21260 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21260L4LH
Minimum Qty (MOQ):	2
NSN:	4030-00-580-6789
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



* See page 2 for technical characteristics

P/N MS21260L4LH Specifications

Thread Class:	3a
Thread Direction:	Left-hand
Inside Diameter:	0.141 Inches Minimum And 0.146 Inches Maximum
Thread Length:	0.516 Inches Minimum And 0.610 Inches Maximum
Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Undercut Diameter:	0.195 Inches Minimum And 0.201 Inches Maximum
Overall Length:	3.957 Inches Minimum And 4.083 Inches Maximum
Plain Shank Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Plain Shank Diameter:	0.245 Inches Minimum And 0.250 Inches Maximum
Accommodated Material Diameter:	0.125 Inches Nominal
Width Across Flats:	0.313 Inches Nominal
Breaking Strength:	2000.0 Pounds Minimum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 303se And Steel Comp 305
Material Document And Classification:	66 Fed Std All Material Responses
Surface Treatment:	Passivate
Style Designator:	Threaded
Thread Series Designator:	Unf

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+stud+terminals/MS21260L4LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.