

**Description**

thread: 1/4-28 left hand, cable diameter: 1/8", swaging, stud, long thread, MS21260 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21260L4LH
Minimum Qty (MOQ):	2
NSN:	4030-00-580-6789
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



\* See page 2 for technical characteristics

## P/N MS21260L4LH Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Left-hand
<b>Inside Diameter:</b>	0.141 Inches Minimum And 0.146 Inches Maximum
<b>Thread Length:</b>	0.516 Inches Minimum And 0.610 Inches Maximum
<b>Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Undercut Diameter:</b>	0.195 Inches Minimum And 0.201 Inches Maximum
<b>Overall Length:</b>	3.957 Inches Minimum And 4.083 Inches Maximum
<b>Plain Shank Length:</b>	1.438 Inches Minimum And 1.500 Inches Maximum
<b>Plain Shank Diameter:</b>	0.245 Inches Minimum And 0.250 Inches Maximum
<b>Accommodated Material Diameter:</b>	0.125 Inches Nominal
<b>Width Across Flats:</b>	0.313 Inches Nominal
<b>Breaking Strength:</b>	2000.0 Pounds Minimum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Steel Comp 303se And Steel Comp 305
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Threaded
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+stud+terminals/MS21260L4LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.