

## Description

5/16-24 left hand thread - 3/16" cable diameter - wire rope terminal - swaging - stud - long thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS21260L6LH
Minimum Qty (MOQ):	1
NSN:	4030-00-580-6780
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



\* See page 2 for technical characteristics

## P/N MS21260L6LH Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Left-hand
<b>Inside Diameter:</b>	0.203 Inches Minimum And 0.208 Inches Maximum
<b>Thread Length:</b>	0.750 Inches Nominal
<b>Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Undercut Diameter:</b>	0.245 Inches Minimum And 0.251 Inches Maximum
<b>Overall Length:</b>	4.549 Inches Minimum And 4.675 Inches Maximum
<b>Plain Shank Length:</b>	1.938 Inches Minimum And 2.000 Inches Maximum
<b>Plain Shank Diameter:</b>	0.354 Inches Minimum And 0.359 Inches Maximum
<b>Accommodated Material Diameter:</b>	0.188 Inches Nominal
<b>Width Across Flats:</b>	0.375 Inches Nominal
<b>Breaking Strength:</b>	4200.0 Pounds Minimum
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Material:</b>	Steel Comp 303se And Steel Comp 305
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Threaded
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas650 Professional/industrial Association Standard

## How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260L6LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.