

Description

5/16-24 right hand thread - 3/16" cable diameter - wire rope terminal - swaging - stud - long thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21260L6RH
Minimum Qty (MOQ):	1
NSN:	4030-00-580-6781
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



P/N MS21260L6RH Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Inside Diameter:	0.223 Inches Nominal
Thread Length:	0.703 Inches Minimum And 0.797 Inches Maximum
Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Undercut Diameter:	0.245 Inches Minimum And 0.251 Inches Maximum
Overall Length:	4.549 Inches Minimum And 4.675 Inches Maximum
Plain Shank Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Plain Shank Diameter:	0.354 Inches Minimum And 0.359 Inches Maximum
Accommodated Material Diameter:	0.188 Inches Nominal
Width Across Flats:	0.375 Inches Nominal
Breaking Strength:	4200.0 Pounds Minimum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Material:	Steel Comp 303se And Steel Comp 305
Material Document And Classification:	66 Fed Std All Material Responses
Surface Treatment:	Passivate
Style Designator:	Threaded
Thread Series Designator:	Unf

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260L6RH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.