



Military-Fasteners.com

P/N MS21260S2LH

Description

6-40 left hand thread, 1/16" cable diameter, wire rope terminal, swaging, stud, short thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21260S2LH
Minimum Qty (MOQ):	5
NSN:	4030-00-580-6797
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



* See page 2 for technical characteristics

P/N MS21260S2LH Specifications

Thread Class:	3a
Thread Direction:	Left-hand
Inside Diameter:	0.078 Inches Minimum And 0.983 Inches Maximum
Thread Length:	0.328 Inches Minimum And 0.422 Inches Maximum
Hole Diameter:	0.063 Inches Minimum And 0.068 Inches Maximum
Undercut Diameter:	0.092 Inches Minimum And 0.098 Inches Maximum
Overall Length:	2.553 Inches Minimum And 2.679 Inches Maximum
Plain Shank Length:	0.969 Inches Minimum And 1.031 Inches Maximum
Plain Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Accommodated Material Diameter:	0.062 Inches Nominal
Width Across Flats:	0.188 Inches Nominal
Breaking Strength:	480.0 Pounds Minimum
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.138 Inches
Material:	Steel Comp 303se And Steel Comp 305
Material Document And Classification:	66 Fed Std All Material Responses
Surface Treatment:	Passivate
Style Designator:	Threaded
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas650 Professional/industrial Association Standard

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260S2LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.