

**Description**

left hand thread 10-32, cable diameter 3/32", wire rope terminal, swaging, stud, short thread, MS21260 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21260S3LH
Minimum Qty (MOQ):	1
NSN:	4030-00-580-6793
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



## P/N MS21260S3LH Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Left-hand
<b>Inside Diameter:</b>	0.109 Inches Minimum And 0.114 Inches Maximum
<b>Thread Length:</b>	0.453 Inches Minimum And 0.547 Inches Maximum
<b>Hole Diameter:</b>	0.063 Inches Minimum And 0.068 Inches Maximum
<b>Undercut Diameter:</b>	0.133 Inches Minimum And 0.139 Inches Maximum
<b>Overall Length:</b>	2.800 Inches Minimum And 2.926 Inches Maximum
<b>Plain Shank Length:</b>	1.188 Inches Minimum And 1.250 Inches Maximum
<b>Plain Shank Diameter:</b>	0.213 Inches Minimum And 0.218 Inches Maximum
<b>Accommodated Material Diameter:</b>	0.094 Inches Nominal
<b>Width Across Flats:</b>	0.250 Inches Nominal
<b>Breaking Strength:</b>	920.0 Pounds Minimum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Steel Comp 303se And Steel Comp 305
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Threaded
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas650 Professional/industrial Association Standard

## How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260S3LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.