

Description

left hand thread 10-32, cable diameter 3/32", wire rope terminal, swaging, stud, short thread, MS21260 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21260S3LH
Minimum Qty (MOQ):	1
NSN:	4030-00-580-6793
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



P/N MS21260S3LH Specifications

Thread Class:	3a
Thread Direction:	Left-hand
Inside Diameter:	0.109 Inches Minimum And 0.114 Inches Maximum
Thread Length:	0.453 Inches Minimum And 0.547 Inches Maximum
Hole Diameter:	0.063 Inches Minimum And 0.068 Inches Maximum
Undercut Diameter:	0.133 Inches Minimum And 0.139 Inches Maximum
Overall Length:	2.800 Inches Minimum And 2.926 Inches Maximum
Plain Shank Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Plain Shank Diameter:	0.213 Inches Minimum And 0.218 Inches Maximum
Accommodated Material Diameter:	0.094 Inches Nominal
Width Across Flats:	0.250 Inches Nominal
Breaking Strength:	920.0 Pounds Minimum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Comp 303se And Steel Comp 305
Material Document And Classification:	66 Fed Std All Material Responses
Surface Treatment:	Passivate
Style Designator:	Threaded
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas650 Professional/industrial Association Standard

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260S3LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.