

Description

left hand thread: 1/4-28, cable diameter: 1/8", swaging, short thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21260S4LH |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4030-00-580-6791 |
| ECCN: | EAR99 |
| National Motor Freight: | 105200, Fittings Cable / Chain / Rope I / S |



* See page 2 for technical characteristics

P/N MS21260S4LH Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Left-hand |
| Inside Diameter: | 0.141 Inches Minimum And 0.146 Inches Maximum |
| Thread Length: | 0.516 Inches Minimum And 0.610 Inches Maximum |
| Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Undercut Diameter: | 0.195 Inches Minimum And 0.201 Inches Maximum |
| Overall Length: | 3.082 Inches Minimum And 3.208 Inches Maximum |
| Plain Shank Length: | 1.438 Inches Minimum And 1.500 Inches Maximum |
| Plain Shank Diameter: | 0.245 Inches Minimum And 0.250 Inches Maximum |
| Accommodated Material Diameter: | 0.125 Inches Nominal |
| Width Across Flats: | 0.313 Inches Nominal |
| Breaking Strength: | 2000.0 Pounds Minimum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Steel Comp 303se And Steel Comp 305 |
| Material Document And Classification: | 66 Fed Std All Material Responses |
| Surface Treatment: | Passivate |
| Style Designator: | Threaded |
| Thread Series Designator: | Unf |

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+stud+terminals/MS21260S4LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.