

Description

1/4-28 left hand thread - 5/32" cable diameter - wire rope terminal - swaging - stud - short thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21260S5LH
Minimum Qty (MOQ):	1
NSN:	4030-00-580-6786
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



* See page 2 for technical characteristics

P/N MS21260S5LH Specifications

Thread Class:	3a
Thread Direction:	Left-hand
Inside Diameter:	0.188 Inches Nominal
Thread Length:	0.578 Inches Minimum And 0.672 Inches Maximum
Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Undercut Diameter:	0.195 Inches Minimum And 0.201 Inches Maximum
Overall Length:	3.376 Inches Minimum And 3.502 Inches Maximum
Plain Shank Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Plain Shank Diameter:	0.292 Inches Minimum And 0.297 Inches Maximum
Accommodated Material Diameter:	0.156 Inches Nominal
Width Across Flats:	0.313 Inches Nominal
Breaking Strength:	2400.0 Pounds Minimum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 303se And Steel Comp 305
Material Document And Classification:	66 Fed Std All Material Responses
Surface Treatment:	Passivate
Style Designator:	Threaded
Thread Series Designator:	Unf

How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260S5LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.