



Military-Fasteners.com

P/N MS21260S5RH

## Description

1/4-28 right hand thread, 5/32" cable diameter, wire rope terminal, swaging, stud, short thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[MS21260-S5RH](#)

SKU / Model:	MS21260S5RH
Minimum Qty (MOQ):	5
NSN:	4030-00-580-6787
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



\* See page 2 for technical characteristics

## P/N MS21260S5RH Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Inside Diameter:</b>	0.172 Inches Minimum And 0.177 Inches Maximum
<b>Thread Length:</b>	0.578 Inches Minimum And 0.672 Inches Maximum
<b>Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Undercut Diameter:</b>	0.195 Inches Minimum And 0.201 Inches Maximum
<b>Overall Length:</b>	3.376 Inches Minimum And 3.502 Inches Maximum
<b>Plain Shank Length:</b>	1.688 Inches Minimum And 1.750 Inches Maximum
<b>Plain Shank Diameter:</b>	0.292 Inches Minimum And 0.297 Inches Maximum
<b>Accommodated Material Diameter:</b>	0.156 Inches Nominal
<b>Width Across Flats:</b>	0.313 Inches Nominal
<b>Breaking Strength:</b>	2400.0 Pounds Minimum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Steel Comp 303se And Steel Comp 305
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Threaded
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas650 Professional/industrial Association Standard

## How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260S5RH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.