

## Description

5/16-24 left hand thread - 3/16" cable diameter - wire rope terminal - swaging - stud - short thread

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21260S6LH                                 |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 4030-00-580-6782                            |
| National Motor Freight: | 105200, Fittings Cable / Chain / Rope I / S |



\* See page 2 for technical characteristics

## P/N MS21260S6LH Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Left-hand   |
| <b>Inside Diameter:</b>                      | 0.203 Inches Minimum And 0.208 Inches Maximum             |
| <b>Thread Length:</b>                        | 0.703 Inches Minimum And 0.797 Inches Maximum             |
| <b>Hole Diameter:</b>                        | 0.098 Inches Minimum And 0.103 Inches Maximum             |
| <b>Undercut Diameter:</b>                    | 0.245 Inches Minimum And 0.251 Inches Maximum             |
| <b>Overall Length:</b>                       | 3.674 Inches Minimum And 3.800 Inches Maximum             |
| <b>Plain Shank Length:</b>                   | 1.938 Inches Minimum And 2.000 Inches Maximum             |
| <b>Plain Shank Diameter:</b>                 | 0.354 Inches Minimum And 0.359 Inches Maximum             |
| <b>Accommodated Material Diameter:</b>       | 0.188 Inches Nominal                                      |
| <b>Width Across Flats:</b>                   | 0.375 Inches Nominal                                      |
| <b>Breaking Strength:</b>                    | 4200.0 Pounds Minimum                                     |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Nominal Thread Size:</b>                  | 0.312 Inches  |
| <b>Material:</b>                             | Steel Comp 303se And Steel Comp 305                       |
| <b>Material Document And Classification:</b> | 66 Fed Std All Material Responses                         |
| <b>Surface Treatment:</b>                    | Passivate   |
| <b>Style Designator:</b>                     | Threaded  |
| <b>Thread Series Designator:</b>             | Unf   |
| <b>Specification/standard Data:</b>          | 80205-nas650 Professional/industrial Association Standard |

## How to Order

Order this wire rope stud terminal from our inventory online by visiting <https://military-fasteners.com/studs/wire+rope+stud+terminals/MS21260S6LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.