

## P/N MS21262-10

### **Description**

Fastener Length: 19/64", Thread: 10-32, Head Width: 5/32", Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2126210

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-926-5597

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21262-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.235 Inches Minimum And 0.265 Inches Maximum
Fastener Length:	0.297 Inches Minimum And 0.327 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS21262-10">https://military-fasteners.com/screws/socket+head+cap+screws/MS21262-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS21262-10">https://military-fasteners.com/screws/socket+head+cap+screws/MS21262-10</a> and selecting the quantity you