

Description

Fastener Length: 3/8", Thread: 8-32, Head Width: 9/64", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2126215
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-946-8340
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21262-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
End Item Identification:	Mk-48 Torpedo;helicopter, Search And Rescue;aircraft, Stratofortress B-52;a-10 Thunderbolt;lamps Mark Iii, Sh-60b Helicop;c-5 Support Equipment;t-37 Support Equipment;t-38 Support Equipment
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21262-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.