

Description

Fastener Length: 27/64", Thread: 10-32, Head Width: 5/32", Thread Length: 27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2126222
Minimum Qty (MOQ):	10
NSN:	5305-00-060-9738
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21262-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Minimum And 0.452 Inches Maximum
Fastener Length:	0.422 Inches Minimum And 0.452 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Qq-s-637 Fed Spec Single Material Response Overall Or 66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21262-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.