

Description

Fastener Length: 3/4", Thread: 1/4-28, Head Width: 3/16", Thread Length: 43/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2126244 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-989-0502 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21262-44 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.664 Inches Minimum And 0.694 Inches Maximum |
| Fastener Length: | 0.735 Inches Minimum And 0.765 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.365 Inches Minimum And 0.375 Inches Maximum |
| Head Height: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.188 Inches Minimum And 0.190 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21262-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.